

/ Descriptions



Schottky Barrier Diode in a TO-220AC Plastic Package.

/ Features

Low power loss,high efficiency .

/ Applications

For use in low voltage,high frequency inverters, free wheeling, and polarity protection applications.

/ Equivalent Circuit**/ Pinning**

PIN1 2 Cathode

PIN 3 Anode

/ h_{FE} Classifications & Marking

See Marking Instructions

/ Absolute Maximum Ratings($T_a=25^\circ\text{C}$)

Parameter	Symbol	Rating	Unit
Peak Repetitive Reverse Voltage	V_{RRM}	100	V
RMS Voltage	V_R	100	V
Average Forward Rectified Current	$I_{F(AV)}$	10	A
Peak forward surge current	I_{FSM}	150	A
Typical Thermal Resistance Junction to Case	$R_{\theta Jc}$	2.0	$^\circ\text{C}/\text{W}$
Junction Temperature Range	T_J	150	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	-55~150	$^\circ\text{C}$

/ Electrical Characteristics($T_a=25^\circ\text{C}$)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Reverse Voltage	V_R	$I_R=10\text{ A}$	100			V
Forward Voltage	V_F	$I_F=10\text{A}$			0.7	V
		$I_F=10\text{A}$ $T_C=125^\circ\text{C}$			0.8	V
		$I_F=20\text{A}$			0.95	V
		$I_F=20\text{A}$ $T_C=125^\circ\text{C}$			0.85	V
Peak Instantaneous Reverse Current	I_{RM}	$V_R=100\text{V}$			0.1	mA
		$V_R=100\text{V}$ $T_C=125^\circ\text{C}$			6	mA

/ Electrical Characteristic Curve




Figure 1. Typical Forward Voltage

Figure 2. Typical Reverse Current




Figure 3. Current Derating, Case

Figure 4. Current Derating, Ambient





Figure 5. Forward Power Dissipation

BRLV10T100AC

Rev.H Apr.-2019

DATA SHEET

/ Marking Instructions




Note:

BR: Company Code

Product Type.

***: Lot No. Code, code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-----|-----|----|----------|---|
| 1 | 150 | 180 | 60 | 90sec; | 1.Preheating:150~180 , Time:60~90sec. |
| 2 | 255 | 5 | 5 | 0.5sec; | 2.Peak Temp.:255 5 , Duration:5 0.5sec. |
| 3 | | | 2 | 10 /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

270 5 10 1 sec. Temp.:270±5°C Time:10±1 sec

/ Packaging SPEC.

/ BULK

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	只袋	袋盒	只盒	盒箱	只箱	袋	盒	箱

/ TUBE

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	只套管	套管盒	只盒	盒箱	只箱	套管	盒	箱

/ Notices