

/ Descriptions

TO-263

Schottky Diode in a TO-263 Plastic Package.

/ Features


Low forward voltage drop, low power losses, High efficiency operation.

/ Applications

OR-ing

DC-DC

For use in high frequency inverters, switching power supplies, freewheeling diodes, OR-ing diode, dc-to-dc converters and reverse battery protection.

/ Equivalent Circuit**/ Pinning**

PIN1 Anode







PIN 2 4 Cathode

PIN 3 Anode


/ h_{FE} Classifications & Marking

See Marking Instructions.

/ Electrical Characteristic Curve



/ Package Dimensions




单位: mm

Dimensions In Millimeters		Symbol		Dimensions In Millimeters		Symbol	
Max	Min			Max	Min		
4.70	4.30	A		1.40	1.00	L	
1.40	1.00	b1		1.40	1.00	b2	



/ Marking Instructions



BR

LV30200

CT:

Note:

BR:

Company Code

LV30200

Product Type.


CT:

Internal Structure

****:

Lot No. Code, code change with Lot No.

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-------|-----|-----------|---|--------------------------------------|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 245±5 | | 5±0.5sec; | 2.Peak Temp.:245±5 , Duration:5±0.5sec. | |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5°C Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	只 卷盘	卷盘 盒	只 盒	盒 箱	只 箱		盒	箱

/ TUBE

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	只 套管	套管 盒	只 盒	盒 箱	只 箱	套管	盒	箱

/ Notices