

/ Descriptions

Schottky Diode in a TO-263 Plastic Package.


/ Features

Low power loss, high efficiency,HF Product.


/ Applications

For use in low voltage,high frequency inverters, free wheeling, and polarity protection applications.

/ Equivalent Circuit



/ Pinning



PIN1 Anode

PIN 2 4 Cathode

PIN 3 Anode

/ h_{FE} Classifications & Marking

See Marking Instructions.

MBRB20200CT

Rev.G Jan.-2024




DATA SHEET


Parameter	Symbol	Rating	Unit
Peak Repetitive Reverse Voltage	V_{RRM}	200	V
Working Peak Reverse Voltage	V_{RWM}	200	V
Average Output Rectified Current	I_o	20	A
Non Repetitive Peak Surge Current	I_{FSM}	120	A
Thermal Resistance Junction to Case	R	3.0	/W
Junction Temperature Range	T_j	150	
Storage Temperature Range	T_{stg}	-55~150	

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
-----------	--------	-----------------	-----	-----	-----	------

/ Electrical Characteristic Curve



/ Package Dimensions




单位：mm

Dimensions In. Millimeters			Dimensions In. Millimeters		
Symbol	Min	Max	Symbol	Min	Max
A	4.30	4.70	E	9.00	9.40
B	1.00	1.40	e1	2.34	2.74
b	0.70	0.90	e2	4.88	5.28
b1	1.15	1.35	L1	15.00	16.00
b2	0.40	0.60	L2	2.24	2.84
C	1.20	1.40	L3	1.20	1.60
D	9.80	10.20			
T0-263					



/ Marking Instructions



Note:

BR:

Company Code

MBRB20200

Product Type

CT:

Internal Structure

****:

Lot No. Code, code change with Lot No

